In the Claims:

Please cancel claim 37.

- 1-25. (Cancelled)
- (Previously Presented) A scanning electrochemical potential microscope
 (SEPM) comprising:
 - a polar solution;
- a sample support that accommodates a sample immersed in the polar solution, wherein a potential gradient is formed at a surface of the sample by an electrical double layer;
- a probe having a tip including a distal end disposed a perpendicular distance from the surface in the electrical double layer; and
- a potential measuring device electrically coupled to said tip that measures a potential across said potential gradient.
- (Original) The SEPM of Claim 26, further comprising a scanning actuator that
 provides relative scanning movement between said probe and said sample.
- 28. (Original) The SEPM of Claim 26, wherein said scanning actuator is a piezoelectric actuator.
- (Original) The SEPM of Claim 26, further comprising a feedback circuit that generates a feedback signal based on said potential.
- (Original) The SEPM of Claim 29, further comprising a Z-actuator that translates the Z-position of said tip in response to said feedback signal.
- (Original) The SEPM of Claim 26, further comprising a Z-actuator that translates the Z-position of the tip in a spectroscopic mode.

{00104908.DOC /}

Reply

Appl, No. 10/052,921 to Chunzeng Li

Page 3

- (Original) The SEPM of Claim 26, further comprising a tuning device that modifies a sample potential at the sample surface.
- (Original) The SEPM of Claim 32, wherein said tuning device is a bipotentiostat.
- (Previously Presented) The SEPM of Claim 26, wherein the polar solution has an associated ionic concentration.
- (Original) The SEPM of Claim 34, wherein said ionic concentration can be modified to tune the operation of the SEPM.
- (Previously Presented) The SEPM of Claim 26, wherein said polar solution is a selected species that has a selected ionic concentration.
 - (Cancelled)
- 38. (Currently Amended) The SEPM of Claim 3740, further comprising a tuning device that modifies a sample potential at the sample surface.
- (Previously Presented) The SEPM of Claim 38, wherein said tuning device is a bi-potentiostat.

Reply

Appl. No. 10/052,921 to Chunzeng Li

Page 4

(Currently Amended) <u>A scanning electrochemical potential microscope (SEPM)</u>
 comprising: The SEPM-of Claim 37.

a sample support that accommodates a sample immersed in a polar solution, wherein a potential gradient is formed at a surface of the sample;

a probe having a tip including a distal end disposed a perpendicular distance from the surface;

a potential measuring device electrically coupled to said tip that measures a potential across said potential gradient; and

wherein the polar solution has an associated ionic concentration, and said potential gradient is formed by an electrical double layer, and said tip is positioned in the electrical double layer.

- 41. (Previously Presented) The SEPM of Claim 40, wherein said ionic concentration can be modified to tune the operation of the SEPM.
- 42. (Currently Amended) The SEPM of Claim 3740, wherein the polar solution is a selected species that has a selected ionic concentration.